



EUROTUNA®



Eurotuna® netting is made from high tenacity Nylon fibres dope dyed (dyed in black during extrusion process).

It is manufactured in Euronete factory with the most advanced netting technology.

All **Eurotuna®** netting is stabilized in the most advanced heat setting machine built in the world for this application.



| Ref. | Runnage m/Kg | Breaking Strength Kgf |
|-----------|-----------------|-----------------------------|
| 4840/2,5 | 375 | 134 |
| 4840/3 | 270 | 170 |
| 4840/4 | 180 | 250 |
| 4840/4,25 | 160 | 282 |
| 4840/4,5 | 140 | 314 |
| 4840/5 | 105 | 390 |
| 4840/5,5 | 90 | 470 |
| 4840/5,75 | 77 | 560 |
| 4840/6 | 67 | 650 |
| 4840/7 | 46 | 760 |
| 4840/8 | 35 | 1050 |
| 4840/10 | 22 | 1450 |

Rev/07/2015

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com

