



12 STRANDS TIPTO TWELVE®



CHEMICAL RESISTANCE – good
SPECIFIC GRAVITY – 0,93
MELTING POINT – approx. 140° C

ABRASION RESISTANCE – very good
UV RESISTANCE - very good
TCLL VALUE – 70,7%

WATER ABSORPTION - 0%
CONSTRUCTION – 12 strand

This rope is available in the diameter range of 16mm up to 48mm and it is the successor of the well-known **Tipto Eight®**.

The construction is different, the material remains the same.

The 12-strands braided construction makes the rope rounder, more stable, more compact and more regular on the surface.

This increases the abrasion resistance and the life-time of the rope even more.

Diameter mm	Weight g/m	MBF kN	MBF tf
16	121	48	4,9
18	155	60,5	6,2
20	189	72,8	7,4
22	231	88	9,0
24	273	103	10,5
28	373	137	14,0
30	428	157	16,0
32	530	177	18,0
36	660	222	22,6
40	756	269	27,4
44	924	321	32,7
48	1090	378	38,5
52	1280	441	45,0
56	1490	508	51,8

Rev1 07/2013

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com

