

8 STRANDS EUROFLEX®



ABRASION RESISTANCE – very good
COLOUR – white with yellow marker

UV-RESISTANCE - good
CONSTRUCTION – 8 strands plaited

MELTING POINT – approx. 165° C / 265°C
SPECIFIC GRAVITY – 1,14

Rev 08/2019

Euroflex® is a rope that has excellent properties of resistance to fatigue caused by tension, abrasion, breaking load and energy absorption. It has a very good cost-performance ratio.

Euroflex® is the answer for the continuous industry demand of ropes with higher strength and smaller diameter. Its excellent handling properties, stiffness and flexibility, make the **Euroflex®** one of the best ropes available today in the market.

Unlike Nylon, **Euroflex®** is not influenced by water, maintaining the same MBL either in dry or wet conditions.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	502	217	21,1
30	558	242	23,4
32	656	281	27,3
36	830	353	34,2
40	1020	432	41,9
44	1240	518	50,3
48	1480	612	59,4
52	1730	714	69,3
56	2010	823	79,9
60	2310	941	91,3
64	2630	1061	103
72	3320	1334	129
80	4110	1628	158
88	4970	1964	191
96	5900	2321	225
104	6890	2699	262
112	8030	3119	303
120	9230	3549	345
128	10500	4022	390
136	11870	4515	438
144	13340	5040	489

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com