

8 STRANDS EUROFLOAT® PREMIUM



Fuel Saving - diameter reduction – high strength.

A floating high performance rope constructed from high strength polypropylene and polyester yarns.

Produced under the latest EN and ISO standards.

Diameter mm	Weight kg/100m	MBF kN
32	53	207
36	67	259
40	85	324
44	99	377
48	120	456
52	141	534
56	162	613
60	188	701
64	216	799
68	245	900
72	275	1000
76	305	1098
80	339	1205
88	411	1470
96	490	1735

SPECIFIC GRAVITY	- 0,98 (FLOATING)
UV - RESISTANCE	- good
ABRASION RESISTANCE	- very good
CHEMICAL RESISTANCE	- good
MELTING POINT	- approx. 165°C/260°C
CONSTRUCTION	- 8-strand plaited
TCLL VALUE	- 75,1%
COLOUR	- off white
MARKER YARN	- two green markers
WATER ABSORPTION	- 0,1%

Rev 01/2019

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com

