

## 8 STRANDS EUROSTEEL®



HIGH ABRASION RESISTANCE  
WATER ABSORPTION – 0%

SPECIFIC GRAVITY – 0,93 (floats)  
HIGH BREAKING STRENGTH

MAXIMUM ELONGATION – 27%  
MELTING POINT – 145° C

**Eurosteel®** 8 strands is a special rope for high traction forces work in marine application.

A rope developed with the highest levels of excellence and quality.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	355	136	13,9
30	405	158	16,1
32	460	172	17,5
36	585	217	22,1
40	720	264	26,9
44	880	312	31,8
48	1040	371	37,8
52	1220	424	43,2
56	1420	484	49,3
60	1630	556	56,7
64	1850	629	64,1
72	2340	787	80,2
80	2900	970	98,9
88	3510	1156	118
96	4170	1361	139
104	4900	1556	159
112	5700	1808	184
120	6500	2069	211
128	7400	2339	238
136	8400	2628	268
144	9400	2927	298

Rev. 0 04/2012

*This data is for guidance purposes only and subject to changes without prior notice.*

Lankhorst Euronete Portugal, SA  
Rua da Cerfil (Cap. Gramaxo) PO Box 1029  
4471-909 Maia - Portugal

Phone: +351 229 619 200  
Fax: +351 229 605 757  
e-mail: sales@grupeeuronete.pt