

## 8 STRANDS NYLON



The standard nylon rope for all purposes.

Produced according to the latest EN and ISO standards. It combines high (dry) strength and excellent abrasion resistance.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	490	207	21,1
32	640	278	28,3
36	810	347	35,4
40	1000	417	42,5
44	1210	493	50,3
48	1440	590	60,2
52	1700	694	70,8
56	1970	778	79,3
60	2260	875	89,2
64	2570	986	101
72	3250	1250	127
80	4010	1556	159
88	4860	1833	187
96	5780	2222	227
104	6780	2500	255
112	7870	2944	300
120	9030	3278	334
128	10100	3681	375
136	11600	4167	425
144	13000	4653	474

CHEMICAL RESISTANCE - good  
 SPECIFIC GRAVITY - 1,14  
 MELTING POINT - approx 218° C

ABRASION RESISTANCE - very good  
 UV - RESISTANCE - good

WATER ABSORPTION - 4%  
 CONSTRUCTION - 8 strands plaited

Rev. 03/2019

*This data is for guidance purposes only and subject to changes without prior notice.*

Lankhorst Euronete Portugal, SA  
 Rua da Cerfil (Cap. Gramaxo) PO Box 1029  
 4471-909 Maia - Portugal

Phone: +351 229 619 200  
 Fax: +351 229 605 757  
 e-mail: euronetesalesdepartment@lankhorsteuronete.com

