



8 STRANDS POLYESTER



The standard Polyester rope for all purposes.
Produced according to latest EN and ISO standards.
It combines strength with an excellent abrasion resistance.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	594	116	11,8
30	682	132	13,5
32	776	150	15,3
36	982	188	19,2
40	1210	230	23,4
44	1470	276	28,1
48	1750	326	33,2
52	2050	380	38,7
56	2380	437	44,5
60	2730	500	51,0
64	3100	566	57,7
72	3930	708	72,2
80	4850	867	88,4
88	5870	1040	106
96	6990	1230	125
104	8220	1430	146
112	9510	1650	168
120	10900	1880	192
128	12400	2130	217
136	14000	2390	244
144	15700	2670	272

CHEMICAL RESISTANCE – good
SPECIFIC GRAVITY – 1,38

ABRASION RESISTANCE – Excellent
UV-RESISTANCE – Excellent

WATER ABSORPTION – 1%
CONSTRUCTION – 8 Strand plaited

Rev1 07/2013

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com

