



8 STRANDS POLYPROPYLENE



Standard 8 strands rope for all purposes, made of polypropylene monofilament.

Produced according to the latest EN and ISO standards.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	354	105	10,7
30	407	119	12,1
32	463	134	13,7
36	586	167	17,0
40	723	204	20,8
44	875	243	24,8
48	1040	286	29,2
52	1220	332	33,8
56	1420	381	38,8
60	1630	433	44,1
64	1850	488	49,7
72	2340	608	62,0
80	2890	740	75,4
88	3500	887	90,4
96	4170	1040	106
104	4890	1210	123
112	5670	1390	142
120	6510	1580	161
128	7410	1780	181
136	8360	2000	204
144	9370	2220	226

CHEMICAL RESISTANCE – good
SPECIFIC GRAVITY – 0,91
MELTING POINT – approx 165° C

ABRASION RESISTANCE – reasonable
UV – RESISTANCE – good
TCLL VALUE – 52%

WATER ABSORPTION - < 0,1%
CONSTRUCTION – 8 strands plaited

Rev1 07/2013

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
Rua da Cerfil (Cap. Gramaxo) PO Box 1029
4471-909 Maia - Portugal

Phone: +351 229 619 200
Fax: +351 229 605 757
e-mail: euronetesalesdepartment@lankhorsteuronete.com

