



## 8 STRANDS TIPTOEIGHT®



The well known high performance rope. It's strength, abrasion resistance and energy absorption ensure a long life-time and economical purchase.

The small diameter and low weight make the handling on board easier.

Diameter mm	Weight g/m	MBF kN	MBF tf
28	373	137	14,0
30	428	157	16,0
32	483	177	18,0
36	614	222	22,6
40	756	269	27,4
44	924	321	32,7
48	1090	378	38,5
52	1280	441	45,0
56	1490	508	51,8
60	1710	578	58,9
64	1940	651	66,4
72	2460	814	83,0
80	3050	992	101
88	3690	1180	120
96	4380	1400	143
104	5150	1620	165
112	5960	1870	191
120	6860	2130	217
128	7790	2410	246
136	8800	2710	276
144	9870	8030	309

CHEMICAL RESISTANCE – good  
 SPECIFIC GRAVITY – 0,93  
 MELTING POINT – approx 140° C

ABRASION RESISTANCE – very good  
 UV – RESISTANCE – very good  
 TCLL VALUE – 70,7%

WATER ABSORPTION - 0%  
 CONSTRUCTION – 8 strands plaited

Rev 1 07/2013

*This data is for guidance purposes only and subject to changes without prior notice.*

Lankhorst Euronete Portugal, SA  
 Rua da Cerfil (Cap. Gramaxo) PO Box 1029  
 4471-909 Maia - Portugal

Phone: +351 229 619 200  
 Fax: +351 229 605 757  
 e-mail: euronetesalesdepartment@lankhorsteuronete.com

