

LANKOFORCE® SCS



LANKOFORCE® SCS (single covered strand) , is a new idea to allow easy splicing.

The construction 8 x 1 makes a nice round and because of that has excellent abrasion properties.

This new rope was developed for several applications in fishing, but the most important ones are:

- BRIDLES
- FRAME ROPES
- SWEEPS
- DOOR LEGS
- SLACK LINES

Diameter mm	Weight g/m	MBF kN	MBF tf
20	340	180	18,4
22	380	210	21,4
24	450	275	28,0
28	490	321	32,7
32	535	435	44,4
36	700	595	60,7
40	1 080	750	76,5
44	1 250	920	93,8
48	1 450	1 120	114,2

CONSTRUCTION - 8 strand braided S.C.S
 SPECIFIC GRAVITY - 0,97
 UV RESISTANCE - excellent
 ABRASION RESISTANCE - very good
 CHEMICAL RESISTANCE - good
 MELTING POINT CORE - approx 147°C
 MELTING POINT JACKET - approx 140°C
 WATER ABSORPTION - 0%
 TOLL VALUE - 100%
 COLOUR - yellow

Euroneema® becomes LANKOFORCE®

This is a name change only.
 The specifications of the former Euroneema® ropes are exactly the same as those of the LANKOFORCE® ropes bellow.



Rev 08/2016

This data is for guidance purposes only and subject to changes without prior notice.

Lankhorst Euronete Portugal, SA
 Rua da Cerfil (Cap. Gramaxo) PO Box 1029
 4471-909 Maia - Portugal

Phone: +351 229 619 200
 Fax: +351 229 605 757
 e-mail: euronetesalesdepartment@lankhorsteuronete.com

