



## EURALPACT®



Trawl wire ropes made of high quality steel with special zinc and aluminium coating to protect from corrosion.

The wire ropes are processed and constructed with the latest technology, combining strength, fatigue resistance and protection from corrosion characteristics in an excellent way.

### EURAL® COATED COMPACTED STEEL WIRE ROPE DUAL TENSILE (1570/1770 N/mm<sup>2</sup>)

#### 6X19 S FIBER CORE

Diameter mm	Weight Kg/100m	MBF kN
10	41	62
12	57	88
14	80	122
15	90	138
16	104	158
18	132	200
19	146	225
20	164	252
22	196	301
24	238	361
26	277	423
28	312	485
30	363	557

#### 6X 19 S STEEL CORE

Diameter mm	Weight Kg/100m	MBF kN
14	90	133
15	101	149
16	117	175
19	165	243
20	184	270
22	220	323
24	266	386
25,4	297	439
26	310	455
28	351	527
30	408	597
32	474	740
34	532	832
35	568	887
36	604	944

Rev 11/2018

*This data is for guidance purposes only and subject to changes without prior notice.*

Lankhorst Euronete Portugal, SA  
Rua da Cerfil (Cap. Gramaxo) PO Box 1029  
4471-909 Maia - Portugal

Phone: +351 229 619 200  
Fax: +351 229 605 757  
e-mail: euronetesalesdepartment@lankhorsteuronete.com

